



Sedgewall



Maxpage



Key Features:

- Standalone desktop paging terminal with large LCD
- Built in 4W transmitter with up to 1 mile range
- Numeric messaging via keypad or alphanumeric messaging via optional PS2 keyboard
- Optional IVR telephone prompt interface
- Optional RS232C serial third party integration
- Optional 4 alarm inputs
- Windows software front end

Specifications:

Power Supply	12VDC via mains 110-240VAC 50/60Hz plugpack 25W max
Frequency Range	VHF 148-174 MHz or UHF 433-470 MHz
External Connectors	Telephone Analogue Line, RJ12F Serial RS232C, 300-57600 baud, DB9F Keyboard, PS2F Alarm Inputs, RJ45F Antenna, 50Ω, BNC female
Input Protocols	TAP, ESPA, Tekk, Comp1/2, Scope, Visiplex
Output Protocols	POCSAG 512, 1200 or 2400bps
Channel Spacing	12.5 kHz (Narrow Band) or 25 kHz (Wide Band)
Message Length	200 characters each
Recipient Capacity	1000 pager ID's
Group Capacity	20 groups with up to 10 members per group
Escalation Capacity	2 steps max, 9999 sec configurable delay
Reminder Messages	10 each with configurable time, recipient and message
Dimensions	226 x 160 x 70 mm (8.9 x 6.3 x 2.75")
Weight	1.0 kg (2.2 lb)
Approvals	FCC, CE, RCM, ROHS, IC, EN60950

*Specifications subject to change without notice

For more details visit www.sedgewall.com